



PUMP FLEXIBLES



JP22VS Untied Van Stone Swivel Flange NP16 Pump Connector. Suitable for chilled water, L.T.H.W, M.T.H.W, Steam and Drinking Water applications. Maximum Working pressure 16 Bar. (Working pressure below 3 Bar)

JP23VS Tied Van Stone Oval Flange NP16 Pump Connector. Suitable for chilled water, L.T.H.W, M.T.H.W, Steam and Drinking Water applications. Maximum Working pressure 16 Bar. (Working pressure above 3 Bar)





PUMP FLEXIBLES



JP20BS Stainless Steel Screwed Pump Connector c/w on bspf socket.

Suitable for chilled water, L.T.H.W, M.T.H.W, Steam and Drinking Water applications. Maximum Working pressure 16 Bar.

SIZE	INSTALLED LENGTH			MAX WORKING	TEST
	JP20BS	JP22VS	JP23VS		
15MM	220			16 BAR	24 BAR
20MM	220			16 BAR	24 BAR
25mm	250			16 BAR	24 BAR
32MM	300			16 BAR	24 BAR
40MM	300			16 BAR	24 BAR
50MM	350	130	130	16 BAR	24 BAR
65MM		130	130	16 BAR	24 BAR
80MM		130	130	16 BAR	24 BAR
100MM		130	130	16 BAR	24 BAR
125MM		130	130	16 BAR	24 BAR
150MM		130	130	16 BAR	24 BAR
200MM		200	200	16 BAR	24 BAR
250MM		200	200	16 BAR	24 BAR
300MM		200	200	16 BAR	24 BAR